

**What is Claimed Is:**

1           1.       A method for use in a packet network in which data is transferred over  
2   virtual circuit connections each having an associated sustained data rate guaranteed by  
3   said network, said network allowing data to be transferred over a connection at a data rate  
4   greater than its associated sustained data rate as a function of network load conditions, the  
5   method comprising:

6           (a)     causing said packet network to provision a first virtual circuit connection  
7   over said packet network for transfer of data between a first user and a second user, said  
8   first virtual circuit connection having a first associated sustained data rate;

9           (b)     transferring data between said first user and said second user over said  
10   connection; and

11          (c)     in response to a determination that said transferring is not achieving a  
12   predetermined minimum desired level of data flow, causing said packet network to  
13   automatically and substantially immediately provision a second virtual circuit connection  
14   over said packet network for said transfer of data from said first user to said second user,  
15   said second virtual circuit connection having a second associated sustained data rate that  
16   is greater than said first sustained data rate.

1           2.       The method of claim 1 further comprising  
2           in response to a determination that said transferring is exceeding a predetermined  
3   maximum desired level of data flow, causing said packet network to automatically and  
4   substantially immediately provision a third virtual circuit connection over said packet  
5   network for said transfer of data from said first user to said second user, said third virtual  
6   circuit connection having a third associated sustained data rate that is lower than said  
7   second sustained data rate.

1           3.       The method of claim 2, wherein said network provisions each said virtual

CON

2 circuit connection in response to a respective call setup message indicating the associated  
3 sustained data rate.

1 4. A method of transferring data over a packet network of a type that  
2 guarantees the transfer of data at at least a requested minimum data rate and that transfers  
3 data at greater than the requested rate on a non-guaranteed basis, the method comprising  
4 requesting from said network varying selected minimum data rates during the transfer of  
5 data between first and second parties, said varying minimum data rates being selected as a  
6 function of the actual data flow between said parties and in such a way as to achieve a  
7 desired overall data flow rate.

1 5. The method of claim 4 wherein said requesting comprises causing said  
2 network to provision successive virtual circuit connections to transfer corresponding  
3 successive portions of said data, each connection having a respective requested minimum  
4 data rate.

1 6. The method of claim 5 wherein said causing said network to provision virtual  
2 circuit connections comprises communicating respective call setup messages to said network.